

TIMBERLINE HT TREE SHEAR

SUPER DURABLE

Patent Pending



**Full 110°
Rotation**

- Fastest cycle time available.
- Made in the USA from **1" High Tensile Steel Plate**.
- Quick attach coupler or pin on couplers for skid steers, tractors, telehandlers, backhoes and wheeled loaders.
- Single 1 1/4" blade eliminates complicated adjustments and sharpening and normally causes tree to fall to the left.
- Unique serrated tooth configuration holds tree during cutting cycle.
- All major pivot points are **machined and greaseable** for long life.
- 2400 PSI or greater hydraulic pressure recommended for best results.
- Weight - 1250 lbs.

The Timberline HT Tree Shear makes it easy to:

- Reach over fences and other obstacles to cut off branches.
- Cut trees laying on the ground into firewood.
- Cut and trim a stand of trees in just minutes.

**Same Day Shipping -
Ship Nationwide**

ARROW
Material Handling Products



1620 OAKLAND ST.
KANSAS CITY, MO 64126-2893
TOLL FREE (800) 821-7563
(816) 231-4410 fax: (816) 241-9137
e-mail: sales@arrowforklift.com

www.arrowforklift.com

TIMBERLINE HT

TREE SHEAR



HYDRAULIC TILT

Operates with
EXISTING
HYDRAULICS

It's Tough...And Built to Last First in Design & Performance

- Cuts 14" tree at ground level in 5.5 seconds.
- Rotates to cut up, hold and move felled trees.
- Reach high to trim large branches.
- Narrower shear gets into tight spaces.

See reverse side for specifications.



Find out more about the Timberline HT Tree Shear at

www.arrowforklift.com